

AD-A038 953

WISCONSIN UNIV MADISON MATHEMATICS RESEARCH CENTER

F/G 12/2

AN EFFICIENT COMPUTATIONAL PROCEDURE FOR SOLVING THE MULTI-FACI--ETC(U)

FEB 77 H JUEL, R LOVE

DAAG29-75-C-0024

UNCLASSIFIED

MRC-TSR-1720

NL

1 OF 1  
AD  
A038953



END

DATE  
FILMED

5-77

ADA 038953

MRC Technical Summary Report # 1720

AN EFFICIENT COMPUTATIONAL  
PROCEDURE FOR SOLVING THE MULTI-  
FACILITY RECTILINEAR FACILITIES  
LOCATION PROBLEM

Henrik Juel and Robert Love

12

Mathematics Research Center  
University of Wisconsin-Madison  
610 Walnut Street  
Madison, Wisconsin 53706

February 1977

(Received December 28, 1976)

See 1473

Approved for public release  
Distribution unlimited



DDC FILE COPY

Sponsored by  
U. S. Army Research Office  
P. O. Box 12211  
Research Triangle Park  
North Carolina 27709

UNIVERSITY OF WISCONSIN - MADISON  
MATHEMATICS RESEARCH CENTER

AN EFFICIENT COMPUTATIONAL PROCEDURE FOR SOLVING THE  
MULTI-FACILITY RECTILINEAR FACILITIES LOCATION PROBLEM<sup>†</sup>

Henrik Juel and Robert Love<sup>\*</sup>

Technical Summary Report #1720  
February 1977

ABSTRACT

The multi-facility location problem with rectilinear distances is considered. A necessary and sufficient optimality condition is stated and proved. An algorithm is developed and computational results are given. A new lower bound for multi-facility problems with  $l_p$  distances is also given.

AMS (MOS) Subject Classification: 90B10

Key Words: Multi-facility, location problem rectilinear distances, algorithm, computational results

Work Unit Number 5 (Mathematical Programming and Operations Research)

ACCESSION BY	
NTIS	<input checked="" type="checkbox"/>
DDC	<input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY	
Dist.	AVAIL. AND OR
A	

<sup>†</sup>Sponsored in part by the United States Army under Contract No. DAAG29-75-C-0024. This research was supported by grants from the Graduate School of the University of Wisconsin; use of the University of Wisconsin Computing Center under these grants was made possible through support, in part, from the National Science Foundation, other U.S. government agencies and the Wisconsin Alumni Research Foundation.

<sup>\*</sup>Visiting Professor in the Department of Management Sciences, University of Waterloo, Waterloo, Ontario in 1976-77.

AN EFFICIENT COMPUTATIONAL PROCEDURE FOR SOLVING THE  
MULTI-FACILITY RECTILINEAR FACILITIES LOCATION PROBLEM<sup>†</sup>

Henrik Juel and Robert Love<sup>\*</sup>

INTRODUCTION

A problem that occurs frequently in the area of facilities location concerns the optimal location of several new facilities in relation to a set of existing facilities. The problem that is addressed here is the one in which distances can be considered to be rectangular. A typical situation occurs when one or more new machines must be located on a plant floor on which there are existing machines and storage areas. The floor is arranged in a rectangular grid such that material movement must take place parallel to two orthogonal axes. The objective is to minimize the total material flow costs between the new machines and the existing machines and storage areas. Other applications include the location of service facilities inside office buildings, the location of factories, warehouses and postal stations in urban areas and the design of piping and wiring circuits. Further discussions of applications are found in reference 9.

A practical application involving the location of two new facilities in relation to three existing manufacturing departments is given by Love and Yerex.<sup>5</sup> For this relatively small problem it was possible to use linear programming as the solution technique using a formulation developed by Wesolowsky and Love<sup>9</sup> and Cabot et. al.<sup>1</sup>

---

<sup>†</sup>Sponsored in part by the United States Army under Contract No. DAAG29-75-C-0024. This research was supported by grants from the Graduate School of the University of Wisconsin; use of the University of Wisconsin Computing Center under these grants was made possible through support, in part, from the National Science Foundation, other U.S. government agencies and the Wisconsin Alumni Research Foundation.

<sup>\*</sup>Visiting Professor in the Department of Management Sciences, University of Waterloo, Waterloo, Ontario in 1976-77.



For larger problems, however, the linear programming formulation of the location problem may give rise to extremely large numbers of variables and equations. As an example, consider a problem with  $m=350$  existing facilities and  $n=70$  new facilities. The linear programming primal has  $2mn + n^2 = 53,900$  variables and  $mn + n(n-1)/2 = 26,915$  constraints. Even the more efficient linear programming dual has 26,915 bounded variables and 70 constraints. The direct search approach of Pritsker and Ghare<sup>6</sup> is more appealing from a computational point of view, since much larger problems can be solved than with the linear programming formulation. However, Rao<sup>7</sup> and Wesolowsky<sup>8</sup> have provided counter-examples proving that the Pritsker and Ghare procedure may not reach optimality in all cases. The present work may be viewed as an optimizing implementation of their approach.

In this paper we state and prove necessary and sufficient conditions for optimality in all cases. (These conditions were indicated by Rao using the theory of linear programming.) A solution algorithm is formulated incorporating the conditions, and computation results are given. These indicate that the algorithm is very rapid when large numbers of new facilities are not located at a single point. We also give a new lower bound on the optimal solution to multi-facility problems. This bound is generalized to account for  $l_p$  distances which are discussed by Love,<sup>3</sup> and Love and Morris.<sup>4</sup>

#### PROBLEM AND NOTATION

The multi-facility rectilinear facilities location problem in one dimension can be formulated as:

$$\text{minimize } f(x) = \sum_{j=1}^n \sum_{i=1}^m w_{1ij} |x_j - a_i| + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} |x_i - x_j|.$$

where  $x = (x_1, x_2, \dots, x_n)$ ,  $m$  is the number of existing facilities, and  $n$  is the number of new facilities.  $w_{1ij}$  is the non-negative weight between existing facility  $i$  and new facility  $j$ , for  $1 \leq i \leq m$ ,  $1 \leq j \leq n$ .  $w_{2ij}$  is the non-negative weight between new facilities  $i$  and  $j$ , for  $1 \leq i < j \leq n$ .  $a_i$  is the (one-dimensional) location of existing facility  $i$ , for  $1 \leq i \leq m$ .  $x_j$  is the (one-dimensional) location of new facility  $j$ , to be determined, for  $1 \leq j \leq n$ . It suffices to consider the problem in one dimension, since an unconstrained problem in more dimensions can be decomposed into one-dimensional problems<sup>9</sup>. It is convenient to assume  $a_1 < a_2 < \dots < a_m$  and to define  $w_{2ji} = w_{2ij}$  for  $1 \leq i < j \leq n$ . Let us denote by a current solution a situation in which each new facility coincides with some existing facility. It suffices to consider current solutions, since an optimal solution exists which is a current solution.<sup>1</sup>

For a current solution  $x = (x_1, x_2, \dots, x_n)$ , let  $s_k$  denote the index-set of new facilities currently coinciding with existing facility  $k$ , that is:

$s_k = s_k(x) = \{j: x_j = a_k\}$  for  $1 \leq k \leq m$ . Finally, let  $f'(x; y)$  denote the directional derivative of the convex function  $f$  at the point  $x = (x_1, x_2, \dots, x_n)$  in the direction  $y = (y_1, y_2, \dots, y_n)$ , that is,  $f'(x; y) = \lim_{h \rightarrow 0+} \frac{f(x+hy) - f(x)}{h}$ .

For the objective function of the multi-facility rectilinear facilities location problem, at a current solution  $x$ , we obtain:<sup>2</sup>

$$f'(x; y) = \sum_{k=1}^m \left[ \sum_{j \in s_k} b_j y_j + \sum_{j \in s_k} \sum_{\substack{i \in s_k \\ i < j}} w_{2ij} |y_i - y_j| + \sum_{j \in s_k} w_{1kj} |y_j| \right],$$

where  $b_j$  denotes the force exerted on new facility  $j$  by the facilities not coinciding with it, that is,

$$b_j = b_j(x) = \sum_{\substack{i=1 \\ i \neq k}}^m w_{1ij} \text{sign}(x_j - a_i) + \sum_{\substack{i=1 \\ i \notin s_k}}^n w_{2ij} \text{sign}(x_j - x_i) \quad \text{for } j \in s_k, 1 \leq k \leq m.$$

Since the objective function is piece-wise linear, the directional derivative is just the increase in the value of the objective function caused by a sufficiently small perturbation of the current solution. That is,  
 $f'(x;y) = f(x+y) - f(x)$ , provided that the components of  $y$  are small enough in magnitude that the restriction of  $f$  to the line segment connecting  $x$  and  $x+y$  is linear.

#### NECESSARY AND SUFFICIENT CONDITIONS FOR OPTIMUM

Since the objective function  $f$  is convex, a necessary and sufficient condition for a current solution  $x$  to be an optimal solution is that the directional derivative  $f'(x;y)$  be non-negative for all directions  $y$ . This condition is not particularly operational, and to transform it into a useful result, we need the following:

Fact:

$$g_k(y) = \sum_{j \in s_k} b_j y_j + \sum_{j \in s_k} \sum_{i \in s_k, i < j} w_{2ij} |y_i - y_j| + \sum_{j \in s_k} w_{1kj} |y_j| \geq 0 \text{ for all } y = (y_1, y_2, \dots, y_n)$$

if and only if, for all subsets  $A_k$  of  $s_k$ :  $\left| \sum_{j \in A_k} b_j \right| \leq \sum_{j \in A_k} \sum_{i \notin A_k} w_{2ij} + \sum_{j \in A_k} w_{1kj}$   
 ( $i \notin A_k$  means  $i \in s_k - A_k$ ).

Proof:

The only-if-part follows by setting  $y_j = z$  for  $j \in A_k$  and  $y_j = 0$  for  $j \notin A_k$ .

For the if-part we need 2 intermediate results. First suppose  $z = \min \{y_j : j \in s_k\} < 0$ . Let  $A_k = \{j \in s_k : y_j = z\}$ . Let  $c$  be any real number satisfying  $z + c \leq 0$  and  $z + c \leq y_j$  for  $j \notin A_k$ . Let the vector  $y'$  be given by  $y'_j = y_j + c$  for  $j \in A_k$  and  $y'_j = y_j$  for  $j \notin A_k$ . Then by direct computation:

$$g_k(y) = g_k(y') + c \left( - \sum_{j \in A_k} b_j + \sum_{j \in A_k} \sum_{i \notin A_k} w_{2ij} + \sum_{j \in A_k} w_{1kj} \right).$$

Next suppose  $z = \max \{y_j : j \in A_k\} > 0$ . Let  $A_k = \{j \in A_k : y_j = z\}$ . Let  $c$  be any real number satisfying  $z-c \geq 0$  and  $z-c \geq y_j$  for  $j \notin A_k$ . Let the vector  $y'$  be given by  $y'_j = y_j - c$  for  $j \in A_k$  and  $y'_j = y_j$  for  $j \notin A_k$ . Then by direct computation

$$g_k(y) = g_k(y') + c \left( \sum_{j \in A_k} b_j + \sum_{j \in A_k} \sum_{i \notin A_k} w_{2ij} + \sum_{j \in A_k} w_{1kj} \right).$$

Now, for any given  $y$  we can apply these results repeatedly with  $c > 0$ , together with the assumption of the if-part, obtaining  $g_k(y) = g_k(0) + \text{non-negative terms} \geq 0$ . This fact, in conjunction with the previously given expression for the directional derivative, proves the following.

**Result:**

A current solution  $x$  is an optimal solution if and only if for all subsets

$$A_k \text{ of } s_k(x): \left| \sum_{j \in A_k} b_j(x) \right| \leq \sum_{j \in A_k} \sum_{i \in s_k(x) - A_k} w_{2ij} + \sum_{j \in A_k} w_{1kj}, \text{ for } 1 \leq k \leq m.$$

For use in the algorithm, 2 special cases of the result are given.

1. If the subset  $A_k = \{j\}$ , then the condition is:

$$|b_j(x)| \leq \sum_{\substack{i \in s_k(x) \\ i \neq j}} w_{2ij} + w_{1kj}.$$

If this condition is not satisfied, an improved current solution is obtained by moving the single new facility  $j$  from  $a_k$  to  $a_{k-\text{sign}(b_j(x))}$ .

2. If the subset  $A_k = s_k(x)$ , then the condition is:

$$\left| \sum_{j \in s_k(x)} b_j(x) \right| \leq \sum_{j \in s_k(x)} w_{1kj}.$$

If this condition is not satisfied, an improved current solution is obtained by moving the whole cluster of new facilities in  $s_k(x)$  from  $a_k$  to

$$a_{k-\text{sign}\left(\sum_{j \in s_k(x)} b_j(x)\right)}.$$



### ALGORITHM

On the basis of the preceding section, the following algorithm is proposed:

1. Find a current solution.
2. Improve the current solution by moving new facilities one at a time, until no further improvements are possible (using special case 1 of Result).
3. Improve the current solution by moving whole clusters of coinciding new facilities, one whole cluster at a time, until no further improvements are possible (using special case 2 of Result).
4. Check all subsets of each cluster of coinciding new facilities (using Result). If moving some subset improves the current solution, make that move and restart step 4. Otherwise, an optimal solution has been found.

This algorithm has been implemented much like the one by Pritsker and Ghare. Thus, the initial current solution is found by solving  $n$  single-facility problems, ignoring the weights between pairs of new facilities. Any move consists of moving one or more new facilities from the current location to the location of a neighboring existing facility. After each move the  $b_j$ 's are updated, rather than recomputed from the basic data.

### COMPUTATIONAL RESULTS

The algorithm was programmed in Fortran, and some test problems were run on a Univac 1110 computer. The computation times reported here represent CPU time exclusive of compilation and reading or generation of input data. The 2 test problems given by Pritsker and Ghare took .05 seconds each. Eight test problems with  $m=50$  and  $n=10$  were generated, the weights being random numbers between 0 and 99. These problems took an average of .9 seconds each. Most of the time was spent in step 4, since the typical optimal solution involved most or all of the 10

new facilities forming a cluster on or near  $a_{25}$ . Of the 8 problems, in 6 cases the optimal solution was found at step 2, in 1 case at step 3 and in 1 case at step 4. For the typical problem, step 4 just performed the optimality test as intended.

Test problems with  $m=350$  and  $n=70$  were generated with biased weights to avoid the excessive and probably atypical clustering of new facilities. The weights were random numbers between 0 and 9, except that  $w_{lij}$  for  $1 \leq j \leq 70$  and  $5(j-1) + 1 \leq i \leq 5j$  were random numbers between 0 and  $W-1$ . Fourteen problems with  $W=300$  took on the average 1.2 seconds each. In one case the optimal solution was found at step 2, in 4 cases at step 3, and in 9 cases at step 4. Fourteen problems with  $W=400$  took on the average 1.1 seconds each. In no cases was the optimal solution found at step 2, in 9 cases at step 3 and in 5 cases at step 4. In these 28 problems, most of the time was spent in step 2. In some problems with a smaller value of  $W$ , an excessive amount of time was spent in step 4, and the program was terminated before completion. For example, in a problem with  $W=200$ , the solution after step 3 involved a cluster of 21 new facilities. Probably more than 20 minutes would have been spent just to check all the subsets of this cluster. (The computer can check roughly 1000 subsets per second.)

#### ACKNOWLEDGEMENTS

This research was supported by the Graduate School and the Graduate School of Business of the University of Wisconsin, Madison. Use of the University of Wisconsin Computing Center was made possible through support, in part, from the National Science Foundation, other United States Government agencies, and the Wisconsin Alumni Research Foundation through the University of Wisconsin Research Committee.

# REFERENCES

- <sup>1</sup>A. V. CABOT, R. L. FRANCIS and M. A. STARY (1970) A network flow solution to a rectilinear distance facility location problem. AIIE Trans. 2, 132.
- <sup>2</sup>H. JUEL (1975) Properties of location models. Operations Research Technical Report No. 3. Graduate School of Business, University of Wisconsin. May 1975.
- <sup>3</sup>R. F. LOVE (1974) The dual of a hyperbolic approximation to the generalized constrained multi-facility location problem with  $\ell_p$  distances. Mgmt Sci. 21, 22.
- <sup>4</sup>R. F. LOVE and J. G. MORRIS (1975) Solving constrained multi-facility location problems involving  $\ell_p$  distances using convex programming. Ops Res. 23, 581.
- <sup>5</sup>R. F. LOVE and L. YEREX (1976) An application of a facilities location model in the prestressed concrete industry. INTERFACES 6, no. 4, 45.
- <sup>6</sup>A.A.B. PRITSKER and P. M. GHARE (1970) Locating new facilities with respect to existing facilities. AIIE Trans. 2, 290. Errata and revisions (1971) in AIIE Trans. 3, 2.
- <sup>7</sup>M. R. RAO (1973) On the direct search approach to the rectilinear facilities location problem (1973) AIIE Trans. 5, 256.
- <sup>8</sup>G. O. WESOLOWSKY (1972) A note on locating new facilities with respect to existing facilities. Unpublished paper, McMaster University, Hamilton, Ontario.
- <sup>9</sup>G. O. WESOLOWSKY and R. F. LOVE (1971) The optimal location of new facilities using rectangular distances. Ops Res. 19, 124.

# APPENDIX - PROPERTIES OF THE $\ell_p$ FUNCTION

Let  $F_p(x)$  denote the objective function of a multi-facility location problem with  $\ell_p$  distances in  $d$  dimensions:

$$F_p(x) = \sum_{j=1}^n \sum_{i=1}^m w_{1ij} \ell_p(x_j - a_i) + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} \ell_p(x_i - x_j)$$

where  $x = (x_1, x_2, \dots, x_n)$ ,  $x_j = (x_{j1}, x_{j2}, \dots, x_{jd})$  for  $1 \leq j \leq n$ ,  
 $a_i = (a_{i1}, a_{i2}, \dots, a_{id})$  for  $1 \leq i \leq m$  and  $\ell_p(z) = \ell_p(z_1, z_2, \dots, z_d) = \left( \sum_{k=1}^d |z_k|^p \right)^{1/p}$ .

Let  $h_k$  denote the minimal value of the corresponding  $k$ th one-dimensional subproblem:

$$h_k = \min \left\{ \sum_{j=1}^n \sum_{i=1}^m w_{1ij} |x_{jk} - a_{ik}| + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} |x_{ik} - x_{jk}| \right\}, \quad 1 \leq k \leq d.$$

Then a lower bound on the optimal value of the  $d$ -dimensional problem is given by the  $\ell_p$ -norm of the vector  $h = (h_1, h_2, \dots, h_d)$ :  $\min\{F_p(x)\} \geq \ell_p(h)$ . This generalizes a result by Pritsker and Ghare (6), who consider the case  $p=2$ ,  $d=2$ .

The result follows from the triangle inequality for  $\ell_p$ -norms.

$$\begin{aligned} \left( \sum_{k=1}^d |h_k|^p \right)^{1/p} &= \left[ \sum_{k=1}^d \left( \min \left\{ \sum_{j=1}^n \sum_{i=1}^m w_{1ij} |x_{jk} - a_{ik}| + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} |x_{ik} - x_{jk}| \right\} \right)^p \right]^{1/p} \\ &\leq \left[ \sum_{k=1}^d \left( \sum_{j=1}^n \sum_{i=1}^m w_{1ij} |x_{jk} - a_{ik}| + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} |x_{ik} - x_{jk}| \right)^p \right]^{1/p} \\ &\leq \sum_{j=1}^n \sum_{i=1}^m w_{1ij} \left( \sum_{k=1}^d |x_{jk} - a_{ik}|^p \right)^{1/p} + \sum_{i=1}^{n-1} \sum_{j=i+1}^n w_{2ij} \left( \sum_{k=1}^d |x_{ik} - x_{jk}|^p \right)^{1/p} = F_p(x). \end{aligned}$$



REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 1720	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER (9) Technical
4. TITLE (and Subtitle) AN EFFICIENT COMPUTATIONAL PROCEDURE FOR SOLVING THE MULTI-FACILITY RECTILINEAR FACILITIES LOCATION PROBLEM.		5. TYPE OF REPORT & PERIOD COVERED Summary Report, no specific reporting period
7. AUTHOR(s) (10) Henrik Juel and Robert Love		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Mathematics Research Center, University of Wisconsin 610 Walnut Street Madison, Wisconsin 53706		8. CONTRACT OR GRANT NUMBER(s) (15) DAAG29-75-C-0024
11. CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office P.O. Box 12211 Research Triangle Park, North Carolina 27709		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 5 (Mathematical Programming and Operations Research)
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) (12) 12p.		12. REPORT DATE (11) February 1977
		13. NUMBER OF PAGES 9
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report) (14) MRC-TSR-1720 Approved for public release; distribution unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Multi-facility Location problem rectilinear distances Algorithm Computational results		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The multi-facility location problem with rectilinear distances is considered. A necessary and sufficient optimality condition is stated and proved. An algorithm is developed and computational results are given. A new lower bound for multi-facility problems with $(l_p)$ distances is also given. L sub p		